

## METHOD FOR CONSTRUCTING SERVICE PROVIDING SYSTEM

BACKGROUND OF THE INVENTIONField of the Invention

5       The present invention relates generally to a method for constructing a service providing system, such as a system for monitoring an external apparatus. More specifically, the invention relates to a method for constructing a serving providing system using a framework for service providing system, which is  
10 described by an object-oriented language or the like; a service providing system constructed by the method; and a computer readable recording media in which a program for service providing system or a framework for service providing system has been recorded.

15 Description of the Related Art

As a service providing system for providing service for an object system, there is known a monitoring system for exchanging monitoring instructions and monitored results with an external apparatus (an object system) serving as a service  
20 provided object to provide various services, such as the setting of initial data, build-up and tabulation of data, for the external apparatus. Such a monitoring system is generally constructed as a software capable of being executed on a computer system. In such a monitoring system, specification change and extension are  
25 carried out in accordance with the kind of external apparatuses serving as an object to be monitored, the kind of screens for interface provided between the monitoring system and a user, the kind of data used in the external apparatus, and the kind of services provided for the external apparatus.

30       However, any reference models for uniformly expressing the configuration of monitoring systems and service are not conventionally established, so that there are problems in that if specification change or extension is carried out, the architecture of the software is likely to be unstable, and the  
35 reusability and change facility of the software can not easily be ensured.

For example, in conventional monitoring systems, internal

09661916 "091400

data handled in the monitoring system are not distinguished from communication data reflecting a communication protocol between the monitoring system and the external apparatus, and communication data exchanged between the monitoring system and the external apparatus are stored in the monitoring system as they are. The stored data are suitably referred and updated to carry out various services. Therefore, as shown in FIG. 31, if the communication protocol between the monitoring system and the external apparatus is changed, the change of the communication protocol influences the whole monitoring system although the service on the side of the monitoring system is not changed.

Specifically, if the order of items of the communication data and the data structure thereof are changed in accordance with the change of the communication protocol, the order of items of data is changed in the monitoring system, and the data structure thereof is changed therein, for example, from bytes to bits. In addition, such change of the data structure also influences other system configurations in the monitoring system for referring to and updating the data, so that it is required to change methods for referring to and updating the data.

In addition, a sequence itself is sometimes changed in accordance with the change of the communication protocol. For example, if an external apparatus serving as an apparatus to be monitored is changed from an old style apparatus to an advanced apparatus or to an apparatus produced by another company, it is often required to change the sequence in accordance with the setting on the side of the apparatus and so forth. In this case, examples are shown in FIGS. 32A and 32B. As shown in FIGS. 32A and 32B, an external apparatus A uses a sequence wherein if monitoring instructions are issued from the side of a monitoring system, processing is carried out on the side of the external apparatus to simply return monitored results. In addition, an external apparatus B uses a sequence wherein if monitoring instructions are issued from the side of a monitoring system, a receipt (a notice meaning that monitoring is not executed although monitoring instructions are received) is once returned from the external apparatus, and thereafter, processing is

004760" 9T6T9960

actually carried out on the side of the external apparatus to return monitored results. Therefore, if the apparatus is changed between such external apparatuses A and B, it is required to change the sequence.

5

#### SUMMARY OF THE INVENTION

It is therefore an object of the present invention to eliminate the aforementioned problems and to provide a method for constructing a service providing system, such as a monitoring system; a service providing system; and a computer readable recording medium in which a program for service providing system or a framework for service providing system has been recorded, the method, system and program being capable of improving the stability of the architecture of a software against specification change and extension and of improving the reusability and change facility of the software.

In order to accomplish the aforementioned and other objects, according to a first aspect of the present invention, there is provided a method for constructing a service providing system using a framework for service providing system which provides a service for an object system, the method comprising the steps of: preparing a framework for service providing system, which includes a data holding part for holding data relating to an object system, a user interface part for receiving instructions from a user and for presenting data to the user, an object system interface part for exchanging data between the object system interface part and the object system in accordance with a predetermined protocol, and an integrated control part for controlling the data holding part, the user interface part and the object system interface part; preparing a plurality of classes on the basis of each of the data holding part, the user interface part, the object system interface part and the integrated control part of the framework for service providing system; associating the classes with each other; and defining a sequence carried out between the respective classes.

35

In the framework for service providing system, the integrated control part preferably controls data which are held in the data holding part, and connects the data holding part with

09661916 "091400

the user interface part to provide various services for the object system on the basis of data which are given from the user or the object system. In addition, in the framework for service providing system, the object system interface part preferably  
5 converts external data, which are exchanged between the object system interface part and the object system, into a format of intermediate data which is independent of the protocol, and the integrated control part preferably converts the intermediate data into a format of internal data which is handled in the service  
10 providing system, the data holding part and user interface part handling the internal data which have been converted by the integrated control part. Furthermore, the service providing system is preferably a monitoring system for monitoring an external apparatus serving as the object system, a control system  
15 for controlling a controlled apparatus serving as the object system, or an information system for exchanging information between the service providing system and an information system serving as the object system.

According to a second aspect of the present invention,  
20 there is provided a service providing system for exchanging service providing instructions and service provided results between the service providing system and an object system to providing various services for the object system, the service providing system comprising: a data holding part for holding data  
25 which relate to an object system; a user interface part for receiving instructions from a user and for presenting data to the user; an object system interface part for exchanging data between the object system interface part and the object system; and an integrated control part for controlling the data holding  
30 part, the user interface part and the object system interface part, wherein the integrated control part controls data which are held in the data holding part, and connects the data holding part with the user interface part to provide various services for the object system on the basis of data which are given from  
35 the user or the object system.

Preferably, the object system interface part converts external data, which are exchanged between the object system

09661916 091400

interface part and the object system, into a format of intermediate data which is independent of the protocol, and the integrated control part converts the intermediate data into a format of internal data which is handled in the service providing system, the data holding part and user interface part handling the internal data which have been converted by the integrated control part.

According to a third aspect of the present invention, there is provided a computer readable recording medium, in which a program for service providing system has been recorded, the program for service providing system comprising, as means for operating a computer: data holding means for holding data which relate to an object system; user interface means for receiving instructions from a user and for presenting data to the user; object system interface means for exchanging data between the object system interface means and the object system; and integrated control means for controlling the data holding means, the user interface means and the object system interface means, wherein the integrated control means controls data which are held in the data holding means, and connects the data holding means with the user interface means to provide various services for the object system on the basis of data which are given from the user or the object system.

Preferably, the object system interface means converts external data, which are exchanged between the object system interface means and the object system, into a format of intermediate data which is independent of the protocol, and the integrated control means converts the intermediate data into a format of internal data which is handled in the service providing system, the data holding means and user interface means handling the internal data which have been converted by the integrated control means.

According to a fourth aspect of the present invention, there is provided a computer readable recording medium, in which a program for service providing system has been recorded, the program for service providing system comprising, as means for operating a computer: internal system means for realizing various

00112024084400

services which are provided for an object system; object system interface means for exchanging data between the object system interface means and the object system; and integrated control means for controlling the internal system means and the object system interface means, wherein the object system interface means converts external data, which are exchanged between the object system interface means and the object system, into a format of intermediate data which is independent of a protocol, and the integrated converts the intermediate data into a format of internal data which is handled by the internal system.

According to a fifth aspect of the present invention, there is provided a computer readable recording medium, in which a framework for service providing system has been recorded, the framework for service providing system comprising: a data holding part for holding data which relate to an object system; a user interface part for receiving instructions from a user and for presenting data to the user; an object system interface part for exchanging data between the object system interface part and the object system; and an integrated control part for controlling the data holding part, the user interface part and the object system interface part, wherein the integrated control part controls data which are held in the data holding part, and connects the data holding part with the user interface part to provide various services for the object system on the basis of data which are given from the user or the object system.

Preferably, the object system interface part converts external data, which are exchanged between the object system interface part and the object system, into a format of intermediate data which is independent of the protocol, and the integrated control part converts the intermediate data into a format of internal data which is handled in the service providing system, the data holding part and user interface part handling the internal data which have been converted by the integrated control part. In addition, each of the data holding part, the object system interface part and the integrated control part preferably includes a class which is prepared every kind of object systems, and the user interface part preferably includes a class

004160" 9161960

which is prepared every kind of screens for interface. Moreover, the class included in the data holding part is preferably prepared every kind of data, which are used in the object systems, in addition to the kind of the object systems. In addition, the class  
5 included in the integrated control part is preferably prepared every kind of services, which are provided for the object systems, in addition to the kind of the object systems. Furthermore, the class included in the integrated control part preferably includes an upper class, which is prepared every kind of the object systems,  
10 and a lower class which is prepared every kind of services which are provided for the object systems under the upper class. Incidentally, it is preferable that the upper class and the lower class are prepared in accordance with the kind of the object systems and the kind of services when a plurality of object systems  
15 are provided for accomplishing a united process.

Preferably, a class included in the integrated control part controls a class included in the data holding part; a class included in the user interface part updates and refers to the class included in the data holding part; data, which are given  
20 from the user and the object system, are exchanged between the class included in the user interface part and the class included in the integrated control part; and data, which relate to a service provided for the object system, are exchanged between the class included in the integrated control part and the class included  
25 in the object system interface part.

Preferably, when service providing instructions for the object system are given to a class included in a user interface part, the class included in the user interface part reflects data, which relate to service providing instructions, in a class  
30 included in the holding part, and gives a class included in the integrated control part notice of the service providing instructions, and the class included in the integrated control part acquires data of the class included in the data holding part, and transmits data of the class, which is included in the data  
35 holding part, to a class included in the object system interface part, the class included in the object system interface part adding data, which relate to a protocol, to data received from

09061916 091400

the integrated control part. In addition, preferably, when service provided results from the object system are given to a class included in an object system interface part, the class included in the object system interface part deletes data, which  
5 relate to a protocol, from data received from the object system, and gives a class, which is included in the integrated control part, notice of service provided results, the class included in the integrated control part reflecting data, which relate to service provided results, in a class included in the data holding  
10 part, and giving a class, which is included in the user interface, notice of service provided results, and the class included in the user interface part acquiring data, which relate to service provided results, from the class included in the data holding part.

15           Thus, according to the present invention, since a service providing system is constructed using a framework for service providing system which uniformly expresses the construction of a service providing system and services, it is possible to improve the stability of the architecture of a software against  
20       specification change and extension, and it is possible to improve the reusability and change facility of the software, so that it is possible to efficiently develop the service providing system.

In addition, according to the present invention, in the service providing system, the integrated control part controls data which are held in the data holding part, and connects the data holding part with the user interface part to provide various services for the object system on the basis of data which are given from the user or the object system, so that it is possible to reduce the mutual-dependence relation of the respective parts in the monitoring system to localize the modified range in accordance with specification change and extension.

Moreover, according to the present invention, the object system interface part converts external data, which are exchanged between the object system interface part and the object system, 35 into a format of intermediate data which is independent of the protocol, and the integrated control part converts the intermediate data into a format of internal data which is handled

091601  
091602  
091603  
091604  
091605  
091606  
091607  
091608  
091609  
091610  
091611  
091612  
091613  
091614  
091615  
091616  
091617  
091618  
091619  
091620  
091621  
091622  
091623  
091624  
091625  
091626  
091627  
091628  
091629  
091630  
091631  
091632  
091633  
091634  
091635  
091636  
091637  
091638  
091639  
091640  
091641  
091642  
091643  
091644  
091645  
091646  
091647  
091648  
091649  
091650  
091651  
091652  
091653  
091654  
091655  
091656  
091657  
091658  
091659  
091660  
091661  
091662  
091663  
091664  
091665  
091666  
091667  
091668  
091669  
091670  
091671  
091672  
091673  
091674  
091675  
091676  
091677  
091678  
091679  
091680  
091681  
091682  
091683  
091684  
091685  
091686  
091687  
091688  
091689  
091690  
091691  
091692  
091693  
091694  
091695  
091696  
091697  
091698  
091699  
091700  
091701  
091702  
091703  
091704  
091705  
091706  
091707  
091708  
091709  
091710  
091711  
091712  
091713  
091714  
091715  
091716  
091717  
091718  
091719  
091720  
091721  
091722  
091723  
091724  
091725  
091726  
091727  
091728  
091729  
091730  
091731  
091732  
091733  
091734  
091735  
091736  
091737  
091738  
091739  
091740  
091741  
091742  
091743  
091744  
091745  
091746  
091747  
091748  
091749  
091750  
091751  
091752  
091753  
091754  
091755  
091756  
091757  
091758  
091759  
091760  
091761  
091762  
091763  
091764  
091765  
091766  
091767  
091768  
091769  
091770  
091771  
091772  
091773  
091774  
091775  
091776  
091777  
091778  
091779  
091780  
091781  
091782  
091783  
091784  
091785  
091786  
091787  
091788  
091789  
091790  
091791  
091792  
091793  
091794  
091795  
091796  
091797  
091798  
091799  
091800  
091801  
091802  
091803  
091804  
091805  
091806  
091807  
091808  
091809  
091810  
091811  
091812  
091813  
091814  
091815  
091816  
091817  
091818  
091819  
091820  
091821  
091822  
091823  
091824  
091825  
091826  
091827  
091828  
091829  
091830  
091831  
091832  
091833  
091834  
091835  
091836  
091837  
091838  
091839  
091840  
091841  
091842  
091843  
091844  
091845  
091846  
091847  
091848  
091849  
091850  
091851  
091852  
091853  
091854  
091855  
091856  
091857  
091858  
091859  
091860  
091861  
091862  
091863  
091864  
091865  
091866  
091867  
091868  
091869  
091870  
091871  
091872  
091873  
091874  
091875  
091876  
091877  
091878  
091879  
091880  
091881  
091882  
091883  
091884  
091885  
091886  
091887  
091888  
091889  
091890  
091891  
091892  
091893  
091894  
091895  
091896  
091897  
091898  
091899  
091900  
091901  
091902  
091903  
091904  
091905  
091906  
091907  
091908  
091909  
091910  
091911  
091912  
091913  
091914  
091915  
091916  
091917  
091918  
091919  
091920  
091921  
091922  
091923  
091924  
091925  
091926  
091927  
091928  
091929  
091930  
091931  
091932  
091933  
091934  
091935  
091936  
091937  
091938  
091939  
091940  
091941  
091942  
091943  
091944  
091945  
091946  
091947  
091948  
091949  
091950  
091951  
091952  
091953  
091954  
091955  
091956  
091957  
091958  
091959  
091960  
091961  
091962  
091963  
091964  
091965  
091966  
091967  
091968  
091969  
091970  
091971  
091972  
091973  
091974  
091975  
091976  
091977  
091978  
091979  
091980  
091981  
091982  
091983  
091984  
091985  
091986  
091987  
091988  
091989  
091990  
091991  
091992  
091993  
091994  
091995  
091996  
091997  
091998  
091999  
092000  
092001  
092002  
092003  
092004  
092005  
092006  
092007  
092008  
092009  
092010  
092011  
092012  
092013  
092014  
092015  
092016  
092017  
092018  
092019  
092020  
092021  
092022  
092023  
092024  
092025  
092026  
092027  
092028  
092029  
092030  
092031  
092032  
092033  
092034  
092035  
092036  
092037  
092038  
092039  
092040  
092041  
092042  
092043  
092044  
092045  
092046  
092047  
092048  
092049  
092050  
092051  
092052  
092053  
092054  
092055  
092056  
092057  
092058  
092059  
092060  
092061  
092062  
092063  
092064  
092065  
092066  
092067  
092068  
092069  
092070  
092071  
092072  
092073  
092074  
092075  
092076  
092077  
092078  
092079  
092080  
092081  
092082  
092083  
092084  
092085  
092086  
092087  
092088  
092089  
092090  
092091  
092092  
092093  
092094  
092095  
092096  
092097  
092098  
092099  
092100  
092101  
092102  
092103  
092104  
092105  
092106  
092107  
092108  
092109  
092110  
092111  
092112



in the service providing system, the data holding part and user interface part handling the internal data which have been converted by the integrated control part, so that the influence of the change of the communication protocol can be localized in the object system interface part.

In addition, according to the present invention, the class of each of the data holding part, the object system interface part and the integrated control part is prepared every kind of object systems, and the class of the user interface part is prepared every kind of screens for interface, so that it is possible to easily cope with the addition and deletion of the object systems and screens for interface. In addition, if the class of the data holding part is prepared every kind of data, which are used in object systems, in addition to the kind of the object systems, and if the class of the integrated control part is prepared every kind of services, which are provided for object systems, in addition to the kind of the object systems, it is possible to easily cope with the addition and deletion of data and services. Moreover, if the class of the integrated control part is divided into an upper class, which is prepared every kind of object systems, and a lower class which is prepared every kind of services which are provided for the object systems under the upper class, it is possible to easily cope with the addition and deletion of services for the same object system.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be understood more fully from the detailed description given herebelow and from the accompanying drawings of the preferred embodiments of the invention. However, the drawings are not intended to imply limitation of the invention to a specific embodiment, but are for explanation and understanding only.

In the drawings:

FIG. 1 is a block diagram showing a framework for monitoring system (service providing system) for use in a method for constructing a monitoring system according to the present invention;

00112024084400

FIG. 2 is a flow chart for explaining a method for constructing a monitoring system according to the present invention;

FIG. 3 is a block diagram showing an example of a class  
5 structure of a monitoring system constructed according to the  
present invention;

FIG. 4 is a sequence diagram showing an example of the operation of the monitoring system shown in FIG. 3;

FIG. 5 is a sequence diagram showing another example of  
10 the operation of the monitoring system shown in FIG. 3;

FIG. 6 is a block diagram showing a class structure of a first preferred embodiment of a monitoring system constructed according to the present invention;

FIG. 7 is a sequence diagram for explaining the operation  
15 of the monitoring system of FIG. 6 during the starting of the  
system;

FIG. 8 is a sequence diagram for explaining the operation of the monitoring system of FIG. 6 when a setting service is provided;

20        FIG. 9 is a sequence diagram for explaining the operation of the monitoring system of FIG. 6 during the stopping of the system;

FIG. 10 is a conceptual diagram for explaining the operation and effect of the monitoring system shown in FIG. 6;

25           FIG. 11 is a block diagram showing a class structure of  
a second preferred embodiment of a monitoring system constructed  
according to the present invention;

FIG. 12 is a sequence diagram for explaining the operation of the monitoring system of FIG. 11 during the starting of the system;

FIG. 13 is a sequence diagram for explaining the operation of the monitoring system of FIG. 11 when a setting service is provided;

FIG. 14 is a sequence diagram for explaining the operation  
35 of the monitoring system of FIG. 11 when a build-up service is  
provided;

FIG. 15 is a sequence diagram for explaining the operation

of the monitoring system of FIG. 11 during the stopping of the system;

FIG. 16 is a conceptual diagram for explaining the operation and effect of the monitoring system shown in FIG. 11;

5           FIG. 17 is a block diagram showing a class structure of  
a third preferred embodiment of a monitoring system constructed  
according to the present invention;

FIG. 18 is a sequence diagram for explaining the operation of the monitoring system of FIG. 17 during the starting of the system;

FIG. 19 is a sequence diagram for explaining the operation of the monitoring system of FIG. 17 when a status indicating service is provided;

FIG. 20 is a sequence diagram for explaining the operation  
15 of the monitoring system of FIG. 17 during the stopping of the  
system;

FIG. 21 is a conceptual diagram for explaining the operation and effect of the monitoring system shown in FIG. 17;

FIG. 22 is a block diagram showing a class structure of  
20 a fourth preferred embodiment of a monitoring system constructed  
according to the present invention;

FIG. 23 is a sequence diagram for explaining the operation of the monitoring system of FIG. 22 during the starting of the system;

25           FIG. 24 is a sequence diagram for explaining the operation  
of the monitoring system of FIG. 22 when a setting service is  
provided;

FIG. 25 is a sequence diagram for explaining the operation of the monitoring system of FIG. 22 during the stopping of the system;

FIG. 26 is a conceptual diagram for explaining the operation and effect of the monitoring system shown in FIG. 22;

FIG. 27 is a block diagram showing an example of a computer system, to which a method for constructing a monitoring system and a monitoring system according to the present invention are applied;

FIG. 28 is a schematic diagram showing an example of a

[illegible]

monitoring system (a service providing system) according to the present invention;

FIG. 29 is a schematic diagram showing an example of a control system (a service providing system) according to the present invention;

FIG. 30 is a schematic diagram showing an example of an information system (a service providing system) according to the present invention;

FIG. 31 is a schematic diagram for explaining a conventional monitoring system; and

FIGS. 32A and 32B is a schematic diagram showing an example of the change of a communication protocol (the change of a sequence) in a conventional monitoring system.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the accompanying drawings, the preferred embodiments of the present invention will be described below.

First, referring to FIGS. 1 through 5, a preferred embodiment of a service providing system constructing method according to the present invention, and a service providing system constructed by the method will be described. Furthermore, in this preferred embodiment, as an example of a service providing system, a system for monitoring an external apparatus (an object system) will be described. As shown in FIG. 28, a monitoring system 701 is connected to various external apparatuses (apparatuses to be monitored) 703 via communication lines 702, such as a common carrier leased line, Internet, and a radio local area network (LAN), so that information 704 about monitoring instructions (service providing instructions) and monitored results (service provided results) is exchanged between the monitoring system 701 and the external apparatuses 703. Furthermore, the monitoring system 701 is an optional system, such as a road monitoring system, a station monitoring system or an electric power monitoring system.

FIG. 1 shows a framework for monitoring system 1, which is used for a monitoring system constructing method in this preferred embodiment. Furthermore, the framework for monitoring

00112024084400

system 1 is realized as an abstract class described by an object-oriented language.

As shown in FIG. 1, the framework for monitoring system 1 comprises: a model part (a data holding part) 10 for holding data relating to the external apparatuses (see reference number 703 in FIG. 28) which are objects to be monitored; a view part (a user interface part) 20 for accepting user's instructions and for presenting data to the user; a proxy part (an object system interface) 40 for exchanging data between the proxy part 40 and the external apparatuses in accordance with a predetermined communication protocol; and a controller part (an integrated control part) 30 for controlling the model part 10, the view part 20 and the proxy part 40. Furthermore, the model part 10 and the view part 20 constitute internal system means.

Furthermore, in FIG. 1, the controller part 30 is designed to control data which are held in the model part 10, and to connect the model part 10 with the view part 20 to provide various services for the external apparatuses on the basis of data which are given from the user or the external apparatuses. In addition, the proxy part 40 is designed to convert communication data (external data), which are exchanged between the proxy part 40 and the external apparatuses, into intermediate data which do not depend on the communication protocol. In addition, the controller part 30 is designed to convert the intermediate data into an internal data format which is handled in the monitoring system. Moreover, the model part 10 and the view part 20 are designed to handle internal data which have been converted by the controller part 30.

FIG. 2 is a flow chart for explaining a method for constructing a monitoring system using the framework for monitoring system 1 shown in FIG. 1.

As shown in FIG. 2, the model part 10, view part 20, proxy part 40 and controller part 30, which are realized as abstract classes of the framework for monitoring system 1, are first inherited, respectively, to prepare a plurality of concrete classes (capsulated data and operations) (step 101). Then, the respective classes thus prepared are associated with each other (step 102). Finally, a sequence carried out between the

00112024084400

respective classes thus associated is defined (step 103). Furthermore, the static side of the monitoring system is defined at each of steps 101 and 102, and the dynamic side of the monitoring system is defined at step 103.

5           FIG. 3 shows an example of a class structure of the monitoring system which is constructed by the constructing method shown in FIG. 2.

As shown in FIG. 3, the monitoring system includes a plurality of classes which are prepared so as to correspond to the model part 10, view part 20, proxy part 40 and controller part 30 of the framework for monitoring system 1.

Among these parts, the model part 10 includes Model-1 through Model-k classes 11, 12 and 13 prepared every kind of the external apparatuses which are objects to be monitored. Furthermore, the Model-1 through Model-k classes are preferably prepared every kind of data used in the external apparatuses, if necessary. In addition, the view part 20 includes View-1 through View-l classes 21, 22 and 23 prepared every kind of graphical user interface (GUI) screens which are screens for interface. In addition, the proxy part 40 includes Proxy-1 through Proxy-n classes 41, 42 and 43 prepared every kind of the external apparatuses which are objects to be monitored. Moreover, the controller part 30 includes Controller-1 through Controller-m classes 31, 32 and 33 prepared every kind of the external apparatuses which are objects to be monitored. Furthermore, the Controller-1 through Controller-m classes 31, 32 and 33 are preferably prepared every kind of services which are provided for the external apparatus, if necessary. Incidentally, it is preferable that the Controller-1 through Controller-m classes 31, 32 and 33 are prepared in accordance with the kind of the object systems and the kind of services when a plurality of object systems are provided for accomplishing a united process.

Furthermore, the respective classes thus prepared are  
35 associated with each other as shown in FIG. 3. That is, in FIG.  
3, the Controller-1 through Controller-m classes 31, 32 and 33  
of the controller part 30 are associated with each other so as

091516 "091400

to control (including refer and update) the Model-1 through Model-k classes 11, 12 and 13 of the model part 10 (associations 51, 52 and 53). In addition, the View-1 through View-l classes 21, 22 and 23 of the view parts 20 are associated with each other so as to update or refer to the Model-1 through Model-k classes 11, 12 and 13 of the model part 10 (associations 61, 62 and 63). In addition, the View-1 through View-l classes 21, 22 and 23 of the view part 20 are associated with the Controller-1 through Controller-m classes 31, 32 and 33 of the controller part 30 so as to exchange data which are given from the user and the external apparatuses, so that the View-1 through View-l classes 21, 22 and 23 give the Controller-1 through Controller-m classes 31, 32 and 33 notice of a View event (an event on a GUI screen) (associations 71, 72 and 73) and so that the Controller-1 through Controller-m classes 31, 32 and 33 give the View-1 through View-l classes 21, 22 and 23 notice a Proxy event (an event from the external apparatuses) (associations 75, 76 and 77). Moreover, the Controller-1 through Controller-m classes 31, 32 and 33 of the controller part 30 are associated with the Proxy-1 through Proxy-n classes 41, 42 and 43 of the proxy part 40 so as to exchange data which relate to the monitoring of the external apparatuses, so that the Controller-1 through Controller-m classes 31, 32 and 33 give the Proxy-1 through Proxy-n classes 41, 42 and 43 notice of monitoring instructions (associations 81, 82 and 83) and so that the Proxy-1 through Proxy-n classes 41, 42 and 43 give the Controller-1 through Controller-m classes 31, 32 and 33 notice of monitored results (associations 85, 86 and 87). Furthermore, the Model-1 through Model-k classes 11, 12 and 13 of the model part 10 are only referred by other classes, and do not utilize any classes.

FIGS. 4 and 5 show the operation of the monitoring system shown in FIG. 3. Furthermore, FIGS. 4 and 5 are sequence diagrams showing the flow of messages between objects (instances of classes). In these figures, objects are expressed by the blocks in the top stage, and the lapse of time is expressed in the direction of axis of ordinates. In addition, the transmission of each message is expressed by an arrow drawn from an object

to another object.

FIG. 4 shows the operation when monitoring instructions to the external apparatuses, which are objects to be monitored, are given to the class (theView) of the View part 20. In this case, the class (theView) of the view part 20 reflects data, which  
5 relate to the monitoring instructions, in the class (theModel) of the model part 10 (step 111), and then, gives the class (theController) of the controller part 30 notice of monitoring instructions (step 112). Then, the class (theController) of the  
10 controller part 30 acquires data of the class (theModel) of the model part 10 (step 113), and then, transmits data of the class (theModel) of the model part 10 to the class (theProxy) of the proxy part 40 in the form of intermediate data (step 114). Finally, the class (theProxy) of the proxy part 40 adds data, which relate  
15 to the communication protocol, to the data (the intermediate data), and then, transmits the data to the external apparatuses.

FIG. 5 shows the operation when the monitored results from the external apparatus, which are objects to be monitored, are given to the class (theProxy) of the proxy part 40. In this case, the class (theClass) of the proxy part 40 deletes data, which  
20 relate to the communication protocol, from data received from the external apparatuses (step 121), and then, gives the class (theController) of the controller part 30 notice of monitored results in the form of intermediate data (step 122). Then, the class (theController) of the controller part 30 reflects data, which relate to the monitored results, in the class (theModel) of the model part 10 (step 123), and then, gives the class (theView) of the view part 20 notice of the monitored results (step 124). Finally, the class (theView) of the view part 20  
30 acquires data, which relate to the monitored results, from the class (theModel) of the model part 10 (step 125).

Thus, according to this preferred embodiment, since the monitoring system is constructed using the framework for monitoring system 1 for uniformly expressing the monitoring  
35 system configuration and services, it is possible to improve the stability of the architecture of the software against specification change and extension and to improve the reusability

004450 " 9767960



and change facility of the software, so that it is possible to efficiently develop the monitoring system.

In addition, according to this preferred embodiment, in the monitoring system, the controller part 30 controls data which are held in the model part 10, and the model part 10 is associated with the view part 20 to provide various services for the external apparatuses on the basis of data which are given from the user or the external apparatuses. Therefore, it is possible to reduce the mutual-dependence relation of the respective parts in the monitoring system to localize the modified range in accordance with specification change and extension. Specifically, the change relating to the communication protocol can be carried out by modifying the proxy part 40, and the change relating to the GUI screen can be carried out by modifying the view part 20. In addition, the change relating to data in the monitoring system can be carried out by modifying the model part 10, and the change relating to the services of the monitoring system can be carried out by modifying the controller part 30.

Moreover, according to this preferred embodiment, the proxy part 40 of the monitoring system converts communication data, which are exchanged between the proxy part 40 and the external apparatuses, into the intermediate data format which does not depend on the communication protocol, and the controller part 30 converts the intermediate data into the internal data format which is handled in the monitoring system, so that the model part 10 and the view part 20 handle the internal data which have been converted by the controller part 30. Therefore, the influence of the change of the communication protocol can be localized in the proxy part 40.

In addition, according to this preferred embodiment, the classes of the model part 10, proxy part 40 and controller part 30 are prepared every kind of the external apparatuses which are objects to be monitored, and the classes of the view part 20 are prepared every kind of the screens for interface. Therefore, it is possible to easily cope with addition, deletion and so forth in the external apparatuses, the screens for interface and so forth. In addition, the classes of the model part 10 are prepared

004760" 9767960

every kind data, which are used in the external apparatus, in addition to the kind of the external apparatus s which are object to be monitored, and prepared every kind of the services, which are provided for the external apparatuses, in addition to the external apparatuses which are objects to be monitored. Therefore, it is possible to easily cope with the addition, deletion and so forth of data and services. Moreover, the classes of the controller part 30 are divided into the upper classes, which are prepared every kind of the external apparatuses which are objects to be monitored, and the lower classes which are prepared every kind of the services which are provided for the external apparatuses. Therefore, it is possible to easily cope with the addition, deletion and so forth of the services which are provided for the same external apparatus.

Furthermore, in the above described preferred embodiment, the monitoring system can be realized on, e.g., a computer system 610 shown in FIG. 27. The computer system 610 comprises a computer body 611 as well as various peripheral apparatuses which include a display unit 612, such as a CRT, a printer 613, an input unit 614, such as a keyboard or a mouse, a FD drive 616, a CD-ROM drive 617 and a hard disk unit 618. The above described program can be stored in a computer readable recording medium, such as an internal memory 615, a hard disk 618, a flexible disk 619 or a CD-ROM 620, on the computer body 611, and sequentially read out of a central processing unit (CPU) on the computer body 611 to be executed to realize the above described functions.

Furthermore, the recording medium according to the present invention may have any one of recording forms as long as it is a recording medium, which can record programs or frameworks and which can be read by a computer, such as a magnetic disk, a floppy disk, a hard disk, an optical disk (a CD-ROM, a CD-R, a DVD or the like), an optical magnetic disk (an MO or the like), or a semiconductor memory. In addition, the recording media include carrier waves transmitted on a network, and information transmitting media.

In addition, an operation system (OS), a data base management software, and a middleware, such as a network software,

00112024084400

which operate on a computer on the basis of the instructions of a program installed in the computer from the recording medium, may execute part of each processing for realizing this preferred embodiment.

Moreover, the recording media according to the present invention include media independent of the computer, as well as recording media in which a program or framework transmitted via a LAN or Internet has been downloaded to be stored or temporarily stored.

10           In addition, the number of the recording media should not be limited to one, but the processing in this preferred embodiment may be executed by a plurality of media which have any construction.

Preferred embodiments of a monitoring system constructed  
15 by the above described monitoring system constructing method will  
be described below.

### First Preferred Embodiment

Referring to FIGS. 6 through 10, the first preferred embodiment of a monitoring system according to the present invention will be described below. Furthermore, in this first preferred embodiment, it is supposed that the number of external apparatuses serving as objects to be monitored is one, only one kind of data (setting data) exist as internal data used in the external apparatus, and only a setting screen exists as a CUI screen for displaying the data.

FIG. 6 shows a class structure of the first preferred embodiment of a monitoring system according to the present invention.

As shown in FIG. 6, in the monitoring system according to the first preferred embodiment, each of the model part 10, the view part 20, the controller part 30 and the proxy part 40 include a single class. That is, the model part 10 includes a Model-1 class 11 for holding setting data which are used in an external apparatus serving as an object to be monitored. In addition, the view part 20 includes a View-1 class 21 for displaying data of the Model-1 class 11 on the CUI screen. Moreover, the proxy part 40 includes a Proxy-1 class 41 corresponding to the external

apparatus serving as the object to be monitored. In addition, the controller part 30 includes a Controller-1 class 31 for providing a setting service for the external apparatus serving as the object to be monitored.

5 Furthermore, in FIG. 6, the Controller-1 class 31 is associated so as to control (including refer and update) the Model-1 class 11 (association 51). In addition, the view-1 class 21 is associated so as to update and refer to the Model-1 class 11 (association 61). Moreover, the View-1 class 21 is associated  
10 with the Controller-1 class 31 so as to exchange data, which are given from the user and the external apparatus, so that the View-1 class 21 gives the Controller-1 class 31 notice of a View event (an event on the GUI screen) (association 71) and so that the Controller-1 class 31 gives the View-1 class 21 notice of a Proxy  
15 event (an event from the external apparatus) (association 75). In addition, the Controller-1 class 31 is associated with the Proxy-1 class 41 so as to exchange the setting data of the external apparatus, so that the Controller-1 class 31 gives the Proxy-1 class 41 notice of setting instructions (association 81) and so  
20 that the Proxy-1 class 41 gives the Controller-1 class 31 notice of set results (association 85). Furthermore, the Model-1 class 11 is only referred by other classes, and does not utilize any classes.

The operations of the first preferred embodiment of a  
25 monitoring system according to the present invention, which is shown in FIG. 6, when the system is started, when the setting service is provided and when the system is stopped, will be described below.

(Starting Of System)

30 FIG. 7 is a diagram for explaining the operation of the first preferred embodiment of a monitoring system according to the present invention, which is shown in FIG. 6, during the starting of the system (the operation when objects (substances of classes) are generated). Furthermore, FIG. 7 is a sequence  
35 diagram showing the flow of messages between objects. In this figure, objects are expressed by the blocks in the top stage, and the lapse of time is expressed in the direction of axis of

ordinates. In addition, the transmission of each message is expressed by an arrow drawn from an object to another object. Furthermore, in FIG. 7, a main routine, which is called when the monitoring system is started, is also expressed as an object for convenience. Furthermore, the sequence diagrams of FIGS. 8 and 9, which will be shown later, are expressed in accordance with the same rule.

First, the main routine generates a Proxy-1 object (step 211). At this time, the Proxy-1 object carries out a connection processing between the external apparatus and the monitoring system to provide a communication enable state between the external apparatus and the monitoring system. Then, the main routine generates a View-1 object (step 212). Moreover, the main routine generates a Controller-1 object (step 213). At this time, the Controller-1 object receives references of the Proxy-1 object and View-1 object in order to have the association with the Proxy-1 object and the View-1 object. On the other hand, since the Controller-1 object controls the Model-1 object, the Controller-1 object generates a Model-1 object (step 214). Subsequently, the Controller-1 object associates itself with the Proxy-1 object (step 215). Moreover, the Controller-1 object associates itself and the Model-1 object with the View-1 object (step 216).  
(Setting Service)

FIG. 8 is a sequence diagram for explaining the operation of the first preferred embodiment of a monitoring system according to the present invention, which is shown in FIG. 6, when a setting service is provided (the operation when setting data are changed on the CUI screen to be transmitted to an external apparatus serving as an object to be monitored).

First, the View-1 object updates the setting data of the Model-1 object (step 221), and then, gives the Controller-1 object notice of the update of the setting data (step 222). Then, the Controller-1 object acquires the setting data from the Model-1 object (step 223), and then, transmits the setting data to the Proxy-1 object in the form of intermediate data (step 224). Finally, the Proxy-1 object adds data, which relate to the

004T60-091400



the communication protocol between the monitoring system and the external apparatus is changed, it has only to change the proxy part 40, and the change of the communication protocol does not influence the model part 10, the view part 20 and the controller part 30. In addition, the view part 20 can directly refer to data of the model part 10, so that it is not required to copy data in the monitoring system. Moreover, since the view part 20 has only to refer to or update items which are required for the model part 10, the change of displayed items on the GUI screen does not influence the model part 10 even if the displayed items are changed.

Thus, according to the monitoring system in the first preferred embodiment, the influence of the change of the communication protocol can be localized in the proxy part 40, and it is possible to prevent data in the monitoring system from being copied. In addition, it is possible to reduce the dependence between the view part 20 and the model part 10.

### Second Preferred Embodiment

Referring to FIGS. 11 through 16, the second preferred embodiment of a monitoring system according to the present invention will be described below. In this second preferred embodiment, a build-up service for an external apparatus is added to the setting service for the external apparatus in the above described first preferred embodiment, and other basic constructions and operations are substantially the same as those in the above described first preferred embodiment. In the second preferred embodiment, the same reference numbers are given to the same portions as those in the first preferred embodiment, and the detailed description thereof is omitted.

FIG. 11 shows a class structure of the second preferred embodiment of a monitoring system according to the present invention.

As shown in FIG. 11, in the monitoring system according to the second preferred embodiment, the controller part 30 includes a Controller-2 class 32 and a Controller-3 class 33 (lower classes) in addition to the Controller-1 class 31 (upper class). The build-up service added in the second preferred

embodiment is provided for transmitting required initialization data to the external apparatus as initialization. However, if only the Controller-1 class 31 copes with the build-up service as the above described first preferred embodiment, the service is complicated. Therefore, the Controller-1 class 31 prepared every kind of external apparatuses, which are objects to be monitored, is internally divided to prepare the Controller-2 class 32 for providing a build-up service and the Controller-3 class 33 for providing a setting service. Furthermore, the Controller-1 class 31 does not any concrete services, and exchanges data between the controller-1 class 31 and other classes (the Model-1 class 11 and the View-1 class 21).

Furthermore, in FIG. 11, the View-1 class 21 and the Proxy-1 class 41 are associated so as to exchange data between these classes and the Controller-1 class 31 (associations 71, 75, 81 and 85). In addition, the Controller-1 class 31 is associated so as to internally possess the Controller-2 class 32 and the Controller-3 class 33 (associations 88 and 89). In addition, although the initialization data of the external apparatus are expressed as the Model-1 class 11, this Model-1 class 11 is associated so that the Controller-2 in charge of the setting service refers to the Model-11, since this Model-1 class 11 is placed as setting data after the build-up service is executed (association 51). On the other hand, since the Controller-3 class 33 is in charge of the build-up service for setting the initialization data for the external apparatus, the Controller-3 class 33 is associated so as to refer to the Model-1 class 11 (association 52).

The operations of the second preferred embodiment of a monitoring system according to the present invention, which is shown in FIG. 11, when the system is started, when the setting service is provided, when and build-up service is provided and when the system is stopped, will be described below.

(Starting Of System)

FIG. 12 is a diagram for explaining the operation of the second preferred embodiment of a monitoring system according to the present invention, which is shown in FIG. 11, during the

00112024084400



starting of the system (th operation when objects (substances of classes) are generated).

As shown in FIG. 12, the same sequence as that in the first preferred embodiment shown in FIG. 7 is carried out until the  
5 Proxy-1 object, the View-1 object, the Controller-1 object and the Model-1 object are produced (steps 311 through 314). Thereafter, the Controller-1 object sequentially generates the Controller-2 object and Controller-3 object which are internally possessed by the Controller-1 object itself (steps 315 and 316).  
10 At this time, the Controller-2 object and the Controller-3 object receive references of the Controller-1 object and Model-1 object in order to have the association with the Controller-1 object and the Model-1 object. Furthermore, the subsequent associations of the Controller-1 object with the Proxy-1 object and View-1 object are carried out by the same sequence as that  
15 in the first preferred embodiment shown in FIG. 7 (steps 317 and 318).

(Setting Service)

FIG. 13 is a sequence diagram for explaining the operation  
20 of the second preferred embodiment of a monitoring system according to the present invention, which is shown in FIG. 11, when a setting service is provided (the operation when setting data are changed on the CUI screen to be transmitted to an external apparatus serving as an object to be monitored).

25 As shown in FIG. 13, the steps until the View-1 object updates the Model-1 object to give the Controller-1 object notice of the update are carried out by the same sequence as that in the first preferred embodiment shown in FIG. 8 (steps 321 and 322). Thereafter, the Controller-1 object directly transmits the  
30 notice of update, which has been received from the View-1 object, to the Controller-2 object, by which the setting service is actually carried out (step 323). Then, the Controller-2 object acquires the setting data from the Model-1 object (step 324). Then, the Controller-2 object transmits the setting data to the  
35 Controller-1 object in the form of intermediate data in order to transmit the setting data to the Proxy-1 object in the form of the intermediate data (step 325). Furthermore, the subsequent

transmission of the setting data to the Proxy-1 object by the Controller-1 object, and the subsequent addition of data relating to the communication protocol by the Proxy-1 object are carried out by the same sequence as that in the first preferred embodiment shown in FIG. 8 (steps 326 and 327).

(Build-Up Service)

FIG. 14 is a sequence diagram for explaining the operation of the second preferred embodiment of a monitoring system according to the present invention, which is shown in FIG. 11, when a build-up service is provided (the operation when initialization data are transmitted to the external apparatus to display the completion of the sequence on the GUI screen).

First, the Proxy-1 object monitors the status of the external apparatus which is the object to be monitored, and requests of the Controller-1 object that it acquires the initialization data when the external apparatus is built up (step 331). Then, the Controller-1 object directly transmits the request of the transmission, which has been received from the Proxy-1 object, to the Controller-3 object, by which the build-up service is actually carried out (step 332). Then, the Controller-3 object acquires the initialization data from the Model-1 object (step 333). Then, the Controller-3 object transmits the initialization data to the Controller-1 object in order to transmit the initialization data to the Proxy-1 object (step 334). Then, the Controller-1 object transmits the initialization data to the Proxy-1 object in the form of intermediate data (step 335). Thereafter, the Proxy-1 object adds data, which relate to the communication protocol, to the initialization data (the intermediate data) (step 336). Then, the Controller-3 object gives the Controller-1 object notice of the transmission of the initialization data in order to give the View-1 object notice that the initialization data have been transmitted (step 337). Then, the Controller-1 object gives the View-1 object of the transmission of the initialization data (step 338).

(Stopping Of System)

FIG. 15 is a sequence diagram for explaining the operation

00112024084400

of the second preferred embodiment of a monitoring system according to the present invention, which is shown in FIG. 11, during the stopping of the system (the operation when the objects are destroyed).

5 As shown in FIG. 15, although the Controller-1 object, the Model-1 object, the View-1 object and the Proxy-1 object are basically destroyed by the same sequence as that in the first preferred embodiment shown in FIG. 9 (steps 341, 344, 345 and 346), the Controller-1 object sequentially destroys the  
10 Controller-3 object and the Controller-2 object (steps 342 and 343) after the main routine destroys the Controller-1 object (step 341) in this second preferred embodiment.

FIG. 16 is a conceptual diagram for explaining the operation and effect of the second preferred embodiment of a  
15 monitoring system according to the present invention, which is shown in FIG. 11.

As shown in FIG. 16, in the monitoring system according to the second preferred embodiment, the view part 20 and the proxy part 40 exchange data between these parts and the Controller-1  
20 class of the controller part 30, and services are actually carried out by the Controller-2 class 32 and Controller-3 class 33 which are internally possessed by the Controller-1 class 31 (reference number (C)). Therefore, even if a new service is intended to be added to the same external apparatus, it is possible to easily  
25 cope therewith by adding and deleting Controller classes in accordance with the service.

#### Third Preferred Embodiment

Referring to FIGS. 17 through 21, the third preferred embodiment of a monitoring system according to the present  
30 invention will be described below. In this third preferred embodiment, status data are added as internal data to the setting data in the above described first preferred embodiment, and a status displaying screen is added to the setting screen in the above described first preferred embodiment as the GUI screen for  
35 displaying these data. Other basic constructions and operations are substantially the same as those in the above described first preferred embodiment. In the third preferred embodiment, the

09661916 "091400

same reference numbers are given to the same portions as those in the first preferred embodiment, and the detailed description thereof is omitted.

FIG. 17 shows a class structure of the third preferred embodiment of a monitoring system according to the present invention.

As shown in FIG. 17, in the monitoring system according to the third preferred embodiment, the model part 10 newly includes a Model-2 class 12 for holding the status data of the external apparatus, and the View part 20 newly includes a View-2 class 22 for displaying data of the Model-2 class 12 on the status displaying screen.

Furthermore, in FIG. 17, the status data of the external apparatus are placed as a different kind of data from the setting data for the same external apparatus, and the Controller-1 class 31 and the Model-2 class 12 are associated so that the Controller-1 class 31 refers to the Model-2 class 12 (association 52). In addition, since it is required to display the status data of the external apparatus on the GUI screen, the View-2 class 22 and the Model-2 class 12 are associated so that the View-2 class refers to the Model-2 class 12 (association 62). Furthermore, although the status data and the setting data are displayed on different GUI screens, the external apparatus as an object is the same apparatus. In addition, in order to check whether the setting data and the status data contradict each other and in order to display the results on the GUI screen, the setting service and the status displaying service are realized by the same Controller-1 class 31. The View-2 class 22 and the Controller-1 class 31 are associated so as to exchange data therebetween (associations 72 and 76).

The operations of the third preferred embodiment of a monitoring system according to the present invention, which is shown in FIG. 17, when the system is started, when the status displaying service is provided and when the system is stopped, will be described below. Furthermore, since the operation when the setting service is provided is the same as that in the above described first preferred embodiment, the description thereof

004160-916-091400

is omitted.

(Starting Of System)

FIG. 18 is a sequence diagram for explaining the operation of the third preferred embodiment of a monitoring system according to the present invention, which is shown in FIG. 17, during the starting of the system (the operation when objects (substances of classes) are generated).

As shown in FIG. 18, the same sequence as that in the first preferred embodiment shown in FIG. 7 is carried out until the Proxy-1 object and the View-1 object are produced (steps 411 and 412). Then, the main routine generates the View-2 object (step 413). Moreover, the main routine generates the Controller-1 object (step 414). At this time, the Controller-1 object receives references of the Proxy-1 object, View-1 object and View-2 object in order to have the association with these objects. Then, the Controller-1 object sequentially generates the Model-1 object and Model-2 object which are controlled by the Controller-1 object itself (steps 415 and 416). Furthermore, the subsequent associations of the Controller-1 object with the Proxy-1 object and View-1 object are carried out by the same sequence as that in the first preferred embodiment shown in FIG. 7 (steps 417 and 418). Finally, the Controller-1 object associates itself and the Model-2 object with the Controller-1 object (step 419).

(Status Displaying Service)

FIG. 19 is a sequence diagram for explaining the operation of the third preferred embodiment of a monitoring system according to the present invention, which is shown in FIG. 17, when a status displaying service is provided (the operation when the status of the external apparatus is displayed after the setting data are changed on the GUI screen and after the setting of the external apparatus is changed by the setting service).

First, the Proxy-1 object receives status data of the external apparatus serving as an object to be monitored, and deletes data, which relate to the communication protocol, from the status data (step 412). Then, the Proxy-1 object transmits the status data to the Controller-1 object in the form of intermediate data (step 422). Then, the Controller-1 object

09061916-091400

updates the status data of the Model-2 object on the basis of the intermediate data (step 423). Moreover, the Controller-1 object acquires the setting data from the Model-1 object (step 424). Then, the Controller-1 compares the setting data with the status data to check whether both contradict each other (step 425). At this time, if the setting data and the status data are coincident with each other, this means that the setting has not effectively carried out. The case where both data are coincident with each other will be herein described. Then, the Controller-1 object gives the View-2 object notice of the update of the status data (step 426). Finally, the View-2 object acquires status data from the Model-2 object (step 427) to display the status data on the GUI screen.

(Stopping Of System)

FIG. 20 is a sequence diagram for explaining the operation of the third preferred embodiment of a monitoring system according to the present invention, which is shown in FIG. 17, during the stopping of the system (the operation when the objects are destroyed).

As shown in FIG. 20, although the Controller-1 object and the Proxy-1 object are basically destroyed by the same sequence as that in the first preferred embodiment shown in FIG. 9 (steps 431 and 436), the Controller-1 object sequentially destroys the Model-2 object and the Model-1 object (steps 432 and 433) after the main routine destroys the Controller-1 object (step 431) in this third preferred embodiment. In addition, the main routine sequentially destroys the View-2 object and the View-1 object (steps 434 and 435).

FIG. 21 is a conceptual diagram for explaining the operation and effect of the third preferred embodiment of a monitoring system according to the present invention, which is shown in FIG. 17.

As shown in FIG. 21, in the monitoring system according to the third preferred embodiment, the model part 10 is separated from the controller part 30 for controlling the model part 10, and data of the model part 10 is controlled by the controller part 30 (reference symbol (D)). Therefore, even if data handled

in the monitoring system are added to or deleted from the model part 10, it is possible to easily determine how data are handled in the services provided by the monitoring system.

In addition, the view part 20 can refer to the model part 10 independently of the relationship between the controller part 30 and the model part 10 (reference symbol (E)). Therefore, even if the GUI screen is added and deleted in accordance with the addition and deletion of data, it is possible to easily cope therewith by adding and deleting the View class.

## 10 Fourth Preferred Embodiment

Referring to FIGS. 22 through 26, the fourth preferred embodiment of a monitoring system according to the present invention will be described below. In this fourth preferred embodiment, the same advanced external apparatus is functionally added to the existing external apparatus in the above described first preferred embodiment, and other basic constructions and operations are substantially the same as those in the above described first preferred embodiment. In the fourth preferred embodiment, the same reference numbers are given to the same portions as those in the first preferred embodiment, and the detailed description thereof is omitted.

FIG. 22 shows a class structure of the fourth preferred embodiment of a monitoring system according to the present invention.

25 As shown in FIG. 22, in the monitoring system according to the fourth preferred embodiment, the proxy part 40 includes a Proxy-2 class 42 for communicating with the advanced external apparatus, in addition to the Proxy-1 class 41 for communicating with the old style external apparatus. Since the advanced  
30 external apparatus has the same function as that of the old style external apparatus, any new Controller classes other than the Controller-1 class 31 are not added. Furthermore, the difference between the Proxy-1 class 41 corresponding to the old style external apparatus and the Proxy-2 class 42 corresponding to the  
35 advanced external apparatus is only the communication protocol.

Furthermore, in FIG. 22, the Controller-1 class 31 is associated with each of the Proxy-1 class 41 and the Proxy-2 class

**THE UNIVERSITY OF CHICAGO**

42 (associations 81, 82, 85 and 86). Because the monitoring system must similarly provide services for the old style and advanced external apparatuses. Furthermore, the associations between the Model-1 class 11, the View-1 class 21 and the Controller-1 31 are the same as those in the first preferred embodiment shown in FIG. 6.

The operations of the fourth preferred embodiment of a monitoring system according to the present invention, which is shown in FIG. 22, when the system is started, when a setting service is provided and when the system is stopped, will be described below.

(Starting Of System)

FIG. 23 is a sequence diagram for explaining the operation of the fourth preferred embodiment of a monitoring system according to the present invention, which is shown in FIG. 22, during the starting of the system (the operation when objects (substances of classes) are generated).

As shown in FIG. 23, first, the main routine generates a Proxy-1 object (step 511), and then, generates a Proxy-2 object (step 512). Thereafter, the same sequence as that in the first preferred embodiment shown in FIG. 7 is carried out until a View-1 object, a Controller-1 object and a Model-1 object are generated (steps 513 through 515). At this time, the Controller-1 object receives references of the Proxy-1 object, Proxy-2 object and View-1 object in order to have the associations with the Proxy-1 object, the Proxy-2 object and the View-1 object. Then, the Controller-1 object associates itself with the Proxy-1 object and the Proxy-2 object (steps 516 and 517). Furthermore, the subsequent association of the Controller-1 object with the View-1 object is carried out simultaneously with the sequence in the first preferred embodiment shown in FIG. 7 (step 518).

(Setting Service)

FIG. 24 is a sequence diagram for explaining the operation of the monitoring system of FIG. 22 when a setting service is provided (the operation when setting data are changed on the CUI screen to be transmitted to an external apparatus serving as an object to be monitored).



As shown in FIG. 24, the same sequence as that in the first preferred embodiment shown in FIG. 8 is carried out until the View-1 object updates the setting data of the Model-1 object, gives the Controller-1 object notice of the update, and acquires the setting data from the Model-1 object (steps 521 through 523). Then, it is identified whether the external apparatus, to which the setting data are transmitted, is an old style or advanced external apparatus (step 524). Furthermore, it is assumed that data for identification are included in the setting data. Assuming that the external apparatus, to which the setting data are transmitted, is an advanced external apparatus, the Controller-1 object transmits the setting data to the Proxy-2 object in the form of intermediate data (step 525). Finally, the Proxy-2 object adds data, which relate to the communication protocol, to the setting data (the intermediate data) (step 526), and then, transmits the setting data to the advanced external apparatus.

(Stopping Of System)

FIG. 25 is a sequence diagram for explaining the operation  
20 of the monitoring system of FIG. 22 during the stopping of the  
system (the operation when the objects are destroyed).

As shown in FIG. 25, although the Controller-1 object, the Model-1 object and the View-1 object are basically destroyed by the same sequence as that in the first preferred embodiment shown in FIG. 9 (steps 531 through 534), the main routine sequentially destroys the Model-2 object and the Model-1 object (steps 534 and 535) after destroying the View-1 object (step 533) in the fourth preferred embodiment.

FIG. 26 is a conceptual diagram for explaining the  
30 operation and effect of the monitoring system shown in FIG. 22.

As shown in FIG. 26, in the monitoring system according to the fourth preferred embodiment, the control part 30 and the proxy part 40 are separated from each other, and the proxy part 40 converts the communication data format in accordance with the communication protocol (reference symbol (F)). In addition, the controller part 30 determines which class of the proxy part 40 data are transmitted to (reference symbol (G)). Therefore, even

if the communication protocol of the external apparatus serving as an object to be monitored is changed, it is possible to easily cope therewith by changing the proxy part 40, and the change of the communication protocol does not influence the model part 10, the view part 20 and the controller part 30.

Furthermore, while the monitoring system for monitoring the external apparatus (the object system) has been described as an example of a service providing system in the above described preferred embodiments, the present invention should not be limited thereto, but the invention may be applied to (1) a control system for controlling an apparatus to be monitored (an object system) (see FIG. 29), and (2) an information system for exchanging information between the information system and another information system (an object system) (see FIG. 30). Furthermore, the control systems include optical systems from domestic electrification control systems, such as air conditioners or televisions, to large scale control systems, such as plant control systems. In addition, the information systems include optional systems, such as material procurement systems, pay management systems and customer information systems.

As shown in FIG. 29, a control system 705 is housed in the same housing as that of a controlled apparatus 706 to be controlled. The control system 705 is connected to the controlled apparatus 706 via an internal control line 707. Between the control system 705 and the controlled apparatus 706, information 708 relating to control instructions (service providing instructions) and controlled results (service provided results) is exchanged.

In such a control system 705, the controlled apparatus 706 serving as an object system is a hardware unit, such as a fan, a louver, a conveyance passage or a guard unit, which is provided in the same housing as that of the control system 705. As a protocol thereof, a control protocol for the hardware unit is used. If the controlled apparatus 706 is changed from an old style apparatus to an advanced apparatus or to an apparatus produced by another company, it is required to change the data structure and sequence for the control protocol, so that the same problems as those in the above described monitoring system are caused.

004760" 9T6T9960

However, such problems can be solved by the proxy part 40 for controlling the controlled apparatus 706 similar to the above described monitoring system.

As shown in FIG. 30, an information system 709 is connected to an information system 711 via a communication line 710, such as a common carrier leased line, Internet, or radio local area network (LAN), so that various information (service providing instructions and service provided results) 712 are exchanged between the information systems 709 and 711.

10 In such an information system 709, the information system  
711 serving as an object system is an external system which is  
equal to the information system 709, and a communication protocol  
for exchanging information is used as the protocol. Specifically,  
15 if the communication line 711 is Internet (Web system), HTTP  
(Hyper Text Transfer Protocol) is used as the communication  
protocol, and communication is realized in accordance with a data  
format called HTML (Hyper Text Markup Language). However,  
recently, XML (extensible Markup Language) is widely noticed,  
so that there is some possibility that a new communication  
20 protocol corresponding to this data format is used. Therefore,  
there is the possibility that the same problems as those in the  
above described monitoring system are caused in accordance with  
the change of the communication protocol. However, similar to  
the above described monitoring system and control system, such  
25 problems can be solved by the proxy part 40 for exchanging  
information between the information system 709 and the  
information system 711 serving as an external system.

As described above, according to the present invention, it is possible to improve the stability of the architecture of a software against specification change and extension, and it is possible to improve the reusability and change facility of the software.

While the present invention has been disclosed in terms of the preferred embodiment in order to facilitate better understanding thereof, it should be appreciated that the invention can be embodied in various ways without departing from the principle of the invention. Therefore, the invention should

09-06-1978

36

be understood to include all possible embodiments and modification to the shown embodiments which can be embodied without departing from the principle of the invention as set forth in the appended claims.

00112024084400